

RECEIVED
CENTRAL FAX CENTER
AUG 17 2007

AMENDMENTS TO THE CLAIMS

1. (Currently Amending) A method comprising:

generating client message digests at a client, the client message digests corresponding to
client files stored on a the client, wherein each client message digest
corresponding corresponds to each client file on the client, wherein the client
message digest digests uniquely identifying identify contents of the client files by
performing a cryptographic hash of the contents of the client files via unique
fingerprints corresponding to the client files, and cataloging the client files,
wherein the unique fingerprints are generated the performing of the cryptographic
hash of the contents including generating a unique fingerprint based on
identifying the contents of each the client file files by performing a cryptographic
hash of the contents of the client files, wherein the client files are cataloged by the
client message digests;

generating server message digests corresponding to server files, each server message
digest corresponding to a server file on a server, wherein the server is coupled to
the client over a network;

prior to synchronizing the client files with the server files, matching client file contents
from the client message digests with server file contents from the server message
digests to determine whether the client files and the server files are to be
synchronized;-and

synchronizing the client files and the server files, if the client file contents and the server
file contents do not match;

performing a post-synchronization match of the client message digests with the server
message digests and, if the client message digests do not match the server

message digests, detecting one or more client files corresponding to one or more unmatched client message digests, and tagging the one or more client files; and re-synchronizing the client files and the server files, the re-synchronization including copying the one or more client files to the server such that the client message digests and the server message digests are matched.

2. (Previously Presented) The method of claim 1, wherein the synchronizing of the client files and the server files comprises adding client file contents that are missing on the server to the server.

Claims 3 - 6 (Cancelled)

7. (Previously Presented) The method of claim 1, further comprising combining the client message digests into a single client message digest.

Claims 8-9 (Cancelled)

10. (Currently Amending) A system comprising:

a storage medium; and

a processor coupled with the storage medium, the processor to:

generate client message digests at a client, the client message digests

corresponding to client files stored on the client, wherein each client

message digest corresponding corresponds to each client file on the client,

wherein the client message digest digests uniquely identifying identify

contents of the client files by performing a cryptographic hash of the

contents of the client files via unique fingerprints corresponding to the

client files, and cataloging the client files, wherein the unique fingerprints

are generated the performing of the cryptographic hash of the contents

including generating a unique fingerprintbased on identifying the contents

of each the client file files, wherein the client files are cataloged by the client message digests;

generate server message digests corresponding to server files, each server message digest corresponding to a server file on a server, wherein the server is coupled to the client over a network;

prior to synchronizing the client files with the server files, match client file contents from the client message digests with server file contents from the server message digests to determine whether the client files and the server files are to be synchronized; and

synchronize the client files and the server files, if the client file contents and the server file contents do not match;

perform a post-synchronization match of the client message digests with the server message digests and, if the client message digests do not match the server message digests, detect one or more client files corresponding to one or more unmatched client message digests, and tag the one or more client files; and

re-synchronize the client files and the server files, the re-synchronization including copying the one or more client files to the server such that the client message digests and the server message digests are matched.

11. (Cancelled)

12. (Previously Presented) The system of claim 10, wherein the cryptographic hash comprises 128 to 160 bits.

Claims 13-19 (Cancelled)

20. (Currently Amending) A machine-readable medium comprising instructions which, when executed, cause a machine to:

generate client message digests at a client, the client message digests corresponding to

client files stored on ~~a the~~ client, wherein each client message digest

~~corresponding~~ corresponds to each client file on the client, wherein the client

message digest ~~digests~~ uniquely identifying ~~identify~~ contents of the client files ~~by~~

~~performing a cryptographic hash of the contents of the client files~~ via unique

fingerprints corresponding to the client files, and cataloging the client files,

wherein the unique fingerprints are generated ~~the performing of the cryptographic~~

~~hash of the contents including generating a unique fingerprint based on~~

~~identifying the contents of each the client file files by performing a cryptographic~~

hash of the contents of the client files, wherein the client files are cataloged by the

client message digests;

generate server message digests corresponding to server files, each server message digest

corresponding to a server file on a server, wherein the server is coupled to the

client over a network;

prior to synchronizing the client files with the server files, match client file contents from

the client message digests with server file contents from the server message

digests to determine whether the client files and the server files are to be

synchronized; and

synchronize the client files and the server files, if the client file contents and the server

file contents do not match;

perform a post-synchronization match of the client message digests with the server

message digests and, if the client message digests do not match the server

message digests, detect one or more client files corresponding to one or more unmatched client message digests, and tag the one or more client files; and re-synchronize the client files and the server files. the re-synchronization including copying the one or more client files to the server such that the client message digests and the server message digests are matched.

Claims 21-28 (Cancelled)

29. (Previously Presented) The system of claim 10, wherein the processor is further to add client file contents that are missing on the server to the server.
30. (Previously Presented) The system of claim 10, wherein the processor is further to combine the client message digests into a single client message digest.
31. (Previously Presented) The machine-readable medium of claim 20, wherein the instructions when executed to perform synchronization, further cause the machine to add client file contents that are missing on the server to the server.
32. (Previously Presented) The machine-readable medium of claim 20, wherein the processor is further to combine the client message digests into a single client message digest.